

## NOTES:

- EJIW 18" VALVE BOX TOP WITH COVER
- 2. 6" PVC D3034 SEWER PIPE
- 3. PIPE SIZE-ROMAC 202S STYLE SERVICE SADDLE DOUBLE STRAP STAINLESS STEEL-TAP 2" I.P. THREAD.
- 4. 2" BRASS CLOSE NIPPLE
- 5. 2" D.I. GATE VALVE WITH 2" OPERATING NUT, BOTH ENDS FEMALE I.P. THREADS-AMERICAN FLOW CONTROL
- 6. 2" MUELLER COMPRESSION #110 COUPLING, MALE I.P. THREADS #H15428N.
- 7. 2" HDPE TUBING CTS SIZE SDR 9 (200 PSI).
- 8. IF NEEDED 2" QUARTER BEND UNION, COMPRESSION CONNECTOR CTS O.D. TUBING BOTH ENDS-#H15526N
- 9. 2" GROUND KEY ANGLE METER STOP MUELLER 110 COMPRESSION, FOR CTS O.D. TUBING, METER FLANGE 180 TURN CHECK-LOCK WING-#H14277N.
- 10. ARMORCAST 17" X 30" X 12" POLYMER CONCRETE METER BOX (A6001640PCX12) AND COVER W/ CAST IRON READ LID (A6001947TRC1)
- 11. WATER METERS THAT ALSO PROVIDE FIRE SUPPRESSION MUST BE TAGGED WITH "SUPPLIES FIRE SUPPRESSION." TAG SHALL BE MIN. 2.5" X 5", WEATHERPROOF, HEAVY DUTY RED PLASTIC. PRE-DRILL AND SECURED TO THE METER WITH PLASTIC CABLE TIES.



## City of Astoria Public Works Department 1095 Duane Street

## 2 Inch Water Service Detail

**Date Adopt.** 11/01/12 **Date Rev.** 9/11/17

**Dwg. Name:** W-4 2 Inch Water Service.dwg

DWG. NO.

W-4